# **Low Cost Hot & Cold water Dispenser**

Economic hot & cold water cooler with filtration makes great tasting water from your tap. Eliminates the hassle of 5-gallon bottles. Great for offices and factories.

#### **Features**

- · Two temperature system
  - Cold: 37-50° F, Adjustable Hot: 180° F, Autocontrol LED indicator for hot or cold water on the front panel
- · Individual on/off control switches for cold or hot water on rear panel
- Completely sealed stainless steel cold reservoir and hot tank
- · Convenient, enclosed, no-drip dispensing faucets
- · Safety lock for hot water faucet
- Built-in filtration system is easily accessed for replacement
   Available with Reverse Osmosis filtration system
   Or Standard Dual-Cartridge filtration system
- · Available with ultraviolet or ozone sterilizer

Filter assembly is front door accessible (right).

Executive Gray cabinet available (far right).



RO membrane, 50 GPD MA-4203





### ORDERING

2-Temp Model - 50 GPD Reverse Osmosis		PWC-1000R
2-Temp Model - Standard Filtration		PWC-1000F
Executive Gray Cabinet		add / <b>EG</b>
2-temp Model with UV sterilizer		add /UV
2-temp Model with Ozone sanitizer		add / <b>0Z</b>
2-temp Model w/ ProTekk Leak Detector		add / <b>Idm</b>
Optional stand, adds 6 inches to height		call factory
Cup holder		call factory
Replacement Filters	Sediment	IFA-4035
	GAC Carbon	IFA-4034

## **Specifications**

Weight: 58 lb.

Dimension: 13"W x 15"D x 38"H
Floor to spigot: 28"
Spigot to Drip Tray: 7.5"
Cold tank volume 1 gal

Heating Rate: 1.5 gal/hr 180 °F Cooling Rate: 1.5 gal/hr 37-50 °F

Voltage: 115 VAC

Hot tank volume .5 gal

Power Required: 600w max Meets Energy Star Requirements

#### **Filter System**

Standard Filter 1000F

Stage 1: 5 micron Sediment

Stage 2: 10 micron Activated Carbon

Reverse Osmosis Filter 1000R

Above 2 stages plus

Stage 3: 50-GPD RO Membrane

Automatic tank full control Fully assembled

- connection hardware included

Meets Energy Star Requirements

ADA compliant



